

# PCI-DDA02/12

## Specifications



**MEASUREMENT  
COMPUTING™**

Document Revision 1.0, February, 2010  
© Copyright 2010, Measurement Computing Corporation

---

# Specifications

Typical for 25 °C unless otherwise specified.

Specifications in *italic text* are guaranteed by design.

## Power consumption

Table 1. Power consumption specifications

+5 V operating	1.4 A typical, 2.2 A max
+12 V	6 mA typical, 12 mA max
-12 V	4 mA typical, 6 mA max

## Analog output

Table 2. Analog output specifications

D/A converter type	AD7837B
Resolution	12-bits
Number of channels	2
Output ranges	$\pm 10$ V, $\pm 5$ V, $\pm 2.5$ V, 0 to 10 V, 0 to 5 V, 0 to 2.5 V. Each channel independently programmable.
Data transfer	Programmed I/O
Offset error (calibrated)	$\pm(300 \mu\text{V} + \frac{1}{4} \text{LSB})$
Gain error (calibrated)	$\pm(300 \mu\text{V} + \frac{1}{4} \text{LSB})$
Differential nonlinearity	$\pm 1$ LSB max
Integral nonlinearity	$\pm 1$ LSB max
Monotonicity	12-bits
D/A gain drift	$\pm 2$ ppm/°C
D/A offset drift	$\pm 5 \mu\text{V}/^\circ\text{C}$
Throughput	PC dependent
Settling time (20V step to $\pm \frac{1}{2}$ LSB)	6 $\mu\text{s}$ typ, 10 $\mu\text{s}$ max
Slew rate	5 V/ $\mu\text{s}$
Current drive	$\pm 5$ mA
Output short-circuit duration	25 mA indefinite
Output coupling	DC
Output impedance	0.1 Ohms max
Miscellaneous	<ul style="list-style-type: none"><li>▪ Double buffered output latches</li><li>▪ Update DACs individually or simultaneously (software selectable)</li><li>▪ Power up and reset, all DAC's cleared to 0 volts, <math>\pm 210</math> mV</li></ul>

## Digital input / output

Table 3. Digital I/O specifications

Digital type (main connector)	82C55 mode 0 emulation
	Output: 74S244
	Input: 74LS373
Configuration	4 banks of 8, 4 banks of 4, programmable by bank as input or output
Number of channels	48 I/O
Output high	2.4 volts min @ -15 mA
Output low	0.5 volts max @ 64 mA
Input high	2.0 volts min, 7 volts absolute max
Input low	0.8 volts max, -0.5 volts absolute min
Power-up / reset state	Input mode (high impedance)

## Environmental

Table 4. Environmental specifications

Operating temperature range	0 to 70 °C
Storage temperature range	-40 to 100 °C
Humidity	0 to 90% non-condensing

## Main connector and pin out

Table 5. Board connectors, cables, accessory equipment

Connector type	100-pin, high density connector
Compatible cables	C100FF-x unshielded ribbon cable (x = length in feet)
Compatible accessory products with the C100FF-x cable	CIO-TERM100 CIO-MINI50 (two required)

Table 6. I/O connector pin out

Pin	Signal Name	Pin	Signal Name
1	Vout 0	51	SECONDPORTA Bit 7
2	Analog Ground	52	SECONDPORTA Bit 6
3	Vout 1	53	SECONDPORTA Bit 5
4	Analog Ground	54	SECONDPORTA Bit 4
5	NC	55	SECONDPORTA Bit 3
6	Analog Ground	56	SECONDPORTA Bit 2
7	NC	57	SECONDPORTA Bit 1
8	Analog Ground	58	SECONDPORTA Bit 0
9	NC	59	SECONDPORTB Bit 7
10	NC	60	SECONDPORTB Bit 6
11	NC	61	SECONDPORTB Bit 5
12	NC	62	SECONDPORTB Bit 4
13	NC	63	SECONDPORTB Bit 3
14	NC	64	SECONDPORTB Bit 2
15	NC	65	SECONDPORTB Bit 1
16	NC	66	SECONDPORTB Bit 0
17	NC	67	SECONDPORTC Bit 7
18	NC	68	SECONDPORTC Bit 6
19	NC	69	SECONDPORTC Bit 5
20	NC	70	SECONDPORTC Bit 4
21	NC	71	SECONDPORTC Bit 3
22	NC	72	SECONDPORTC Bit 2
23	NC	73	SECONDPORTC Bit 1
24	NC	74	SECONDPORTC Bit 0
25	NC	75	FIRSTPORTA Bit 7
26	NC	76	FIRSTPORTA Bit 6
27	NC	77	FIRSTPORTA Bit 5
28	NC	78	FIRSTPORTA Bit 4
29	NC	79	FIRSTPORTA Bit 3
30	NC	80	FIRSTPORTA Bit 2
31	NC	81	FIRSTPORTA Bit 1
32	NC	82	FIRSTPORTA Bit 0
33	NC	83	FIRSTPORTB Bit 7
34	NC	84	FIRSTPORTB Bit 6
35	NC	85	FIRSTPORTB Bit 5
36	NC	86	FIRSTPORTB Bit 4
37	NC	87	FIRSTPORTB Bit 3
38	NC	88	FIRSTPORTB Bit 2
39	NC	89	FIRSTPORTB Bit 1
40	NC	90	FIRSTPORTB Bit 0
41	NC	91	FIRSTPORTC Bit 7
42	NC	92	FIRSTPORTC Bit 6
43	NC	93	FIRSTPORTC Bit 5
44	NC	94	FIRSTPORTC Bit 4
45	NC	95	FIRSTPORTC Bit 3
46	NC	96	FIRSTPORTC Bit 2
47	NC	97	FIRSTPORTC Bit 1
48	NC	98	FIRSTPORTC Bit 0
49	NC	99	+5V
50	Digital Ground	100	Digital Ground

**Measurement Computing Corporation**  
**10 Commerce Way**  
**Suite 1008**  
**Norton, Massachusetts 02766**  
**(508) 946-5100**  
**Fax: (508) 946-9500**  
**E-mail: [info@mccdaq.com](mailto:info@mccdaq.com)**  
**[www.mccdaq.com](http://www.mccdaq.com)**